


合成石英DCV(両凹)レンズ

仕様	直径	+0, -0.1mm	表面	M I L 60-40
	中心厚	±0.2mm	偏芯	3分以内
	屈折率	1.4585	設計波長	587.6NM
	F L	±2%	コート	無し



コード	外径(mm)	F L (mm)	B F L (mm)	中心厚(mm)	フチ厚(mm)	金額
V111	5.0	-5.0	-5.34	1.0	1.84	¥15,900
V112	5.0	-7.5	-7.83	1.0	1.84	¥15,900
V113	5.0	-10.0	-10.35	1.0	1.63	¥15,900
V114	5.0	-12.5	-12.84	1.0	1.52	¥15,900
V115	5.0	-15.0	-15.34	1.0	1.42	¥15,900
V116	5.0	-20.0	-20.34	1.0	1.31	¥15,900
V117	5.0	-30.0	-30.34	1.0	1.20	¥15,900
V118	5.0	-40.0	-40.36	1.0	1.16	¥15,900
V119	5.0	-50.0	-50.34	1.0	1.13	¥15,900
V120	10.0	-10.0	-10.35	1.0	3.65	¥26,500
V121	10.0	-15.0	-15.34	1.0	2.70	¥24,700
V122	10.0	-20.0	-20.34	1.0	2.27	¥23,000
V123	10.0	-30.0	-30.34	1.0	1.83	¥21,200
V124	10.0	-40.0	-40.36	1.0	1.63	¥17,700
V125	10.0	-50.0	-50.34	1.0	1.50	¥17,700
V126	10.0	-60.0	-60.70	2.0	2.40	¥17,700
V127	10.0	-80.0	-80.72	2.0	2.30	¥17,700
V128	10.0	-90.0	-90.70	2.0	2.30	¥17,700
V129	10.0	-100.0	-100.67	2.0	2.25	¥17,700
V130	15.0	-15.0	-15.34	1.0	5.10	¥28,300
V131	15.0	-20.0	-20.34	1.0	4.00	¥26,500
V132	15.0	-25.0	-25.36	1.0	3.36	¥24,700
V133	15.0	-30.0	-30.48	1.0	2.96	¥22,900
V134	15.0	-40.0	-40.36	1.0	2.40	¥21,200
V135	15.0	-50.0	-50.34	1.0	2.16	¥19,500
V136	15.0	-60.0	-60.70	2.0	2.96	¥19,500
V137	15.0	-70.0	-70.68	2.0	2.82	¥19,500
V138	15.0	-80.0	-80.72	2.0	2.72	¥19,500
V139	15.0	-90.0	-90.70	2.0	2.64	¥19,500
V140	15.0	-100.0	-100.67	2.0	2.58	¥19,500
V141	20.0	-20.0	-20.34	1.0	6.60	¥35,300
V142	20.0	-30.0	-30.34	1.0	4.60	¥33,600
V143	20.0	-40.0	-40.36	1.0	3.65	¥31,800
V144	20.0	-50.0	-50.34	1.0	3.11	¥28,300
V145	20.0	-60.0	-60.70	2.0	3.74	¥24,700
V146	20.0	-70.0	-70.68	2.0	3.49	¥24,700
V147	20.0	-80.0	-80.72	2.0	3.30	¥24,700
V148	20.0	-90.0	-90.70	2.0	3.16	¥24,700
V149	20.0	-100.0	-100.67	2.0	3.04	¥24,700
V150	30.0	-30.0	-30.71	2.0	10.50	¥44,100
V151	30.0	-40.0	-40.69	2.0	8.20	¥42,400
V152	30.0	-50.0	-50.72	2.0	6.80	¥40,600
V153	30.0	-60.0	-60.70	2.0	6.00	¥37,100
V154	30.0	-70.0	-70.68	2.0	5.44	¥35,300
V155	30.0	-80.0	-80.72	2.0	5.00	¥35,300
V156	30.0	-90.0	-90.70	2.0	4.66	¥35,300
V157	30.0	-100.0	-100.67	2.0	4.40	¥35,300
V158	40.0	-40.0	-40.69	2.0	13.50	¥52,900
V159	40.0	-50.0	-50.72	2.0	10.90	¥51,200
V160	40.0	-60.0	-60.70	2.0	9.30	¥45,900

コード	外径(mm)	FL(mm)	BFL(mm)	中心厚(mm)	フチ厚(mm)	金額
V161	40.0	-70.0	-70.68	2.0	8.20	¥42,400
V162	40.0	-80.0	-80.72	2.0	7.40	¥42,400
V163	40.0	-90.0	-90.70	2.0	6.80	¥40,600
V164	40.0	-100.0	-100.67	2.0	6.30	¥40,600
V165	40.0	-150.0	-150.74	2.0	4.80	¥40,600
V166	40.0	-200.0	-200.69	2.0	4.14	¥40,600
V167	40.0	-300.0	-300.70	2.0	3.42	¥40,600
V168	50.0	-50.0	-50.72	2.0	16.44	¥70,600
V169	50.0	-60.0	-60.70	2.0	13.70	¥67,100
V170	50.0	-70.0	-70.68	2.0	11.90	¥63,600
V171	50.0	-80.0	-80.72	2.0	10.59	¥60,000
V172	50.0	-90.0	-90.70	2.0	9.59	¥52,900
V173	50.0	-100.0	-100.67	2.0	8.81	¥52,900
V174	50.0	-150.0	-150.74	2.0	6.50	¥52,900
V175	50.0	-200.0	-200.69	2.0	5.36	¥52,900
V176	50.0	-300.0	-300.70	2.0	4.23	¥52,900

透過率

(板厚 10mm)

